



## Report on HFR - Vigo Historical data files QA/QC

### Data provider information:

- contributors name: Instituto Hidrografico
- contributors contact: ih.snig.metadados@hidrografico.pt
- acknowledgements: Instituto Hidrografico

System: <b>Vigo</b>
Sites: <b>SUBR, TORA</b>
Data set: <b>Totals</b>
Data source: Totals from the radials combination in de EU Node
Period: <b>2010-Feb-18 - 2016-May-27</b>



Daily data % available during the whole time period

#### **INFO ON QA/QC Settings and Calibration**

%%% QC info for time: 18-Feb-2010 12:30:00

OceanSITES quality flagging for GDOP threshold QC test. Threshold set to 2.5.

%%% QC info for time: 18-Feb-2010 12:30:00

OceanSITES quality flagging for Data density threshold QC test. Threshold set to 3 radials.

%%% QC info for time: 18-Feb-2010 12:30:00

OceanSITES quality flagging for Velocity threshold QC test. Threshold set to 1 m/s.

%%% QC info for time: 18-Feb-2010 12:30:00

OceanSITES quality flagging for variance threshold QC test. Test not applicable to Direction Finding systems. The Temporal Derivative test is applied. Threshold set to 1 m/s.

%%% Last calibration info for time: 25-Jan-2016 06:00:00

SUBR: 2012-12-13T00:00:00Z; TORA: 2012-12-10T00:00:00Z

#### **RESULTS OF HIST DATA INSPECTION**

##### **General comments:**

When data is available the “number of good data” is high with the lowest number for 2015. The main QC flags correspond to GDOP.

year	General comment	Periods to be reflagged	Reason for new flagging	Sugg. Flag
After exchanges with the provided the following periods where reflagged:				
Year	General comment	Periods to be reflagged	Reason	New Flag

Data availability is unstable with remarkable data gaps throughout the whole analysed period from 2010 until 2016. Note that data frequency is every half an hour instead of hourly, therefore the monthly percentages in Figure A have to be divided by 2.

For the dates when data is available the spatio-temporal coverage fits the 80%-80% objective for all the years for almost the whole study area.

The general annual mean pattern shows a cyclonic gyre in the west part of the study area, centered around 42° 13'N, 8° 52'W. In the east of the study area, there are different patterns for the different years but a westward flow, coming from the East is present for all the analyzed years.

##### **Spatial Coverage vs. Temporal coverage: objective of USCG 80-80% data availability**

Period	General comments	Nb. analysed hours	80%-80% obj.
2010	89.3805% spatial availability 80% of the time.	10690	y
2011	95.2212% spatial availability 80% of the time.	13802	y
2012	93.9823% spatial availability 80% of the time.	14272	y
2013	94.8673% spatial availability 80% of the time.	13931	y
2014	98.4071% spatial availability 80% of the time.	10389	y
2015	98.7611% spatial availability 80% of the time.	17202	y

2016	98.2301% spatial availability 80% of the time.	5345	y
------	--	------	---

**Annex I Applied QA/QC tests**

QC Flag Variable name	Short name	Short description
-	Syntax	<b>Syntax</b> check: this test will ensure the proper formatting and the existence of all the necessary fields within the total NetCDF file. This test is performed on the NetCDF files and it assesses the presence and correctness of all data and attribute fields and the correct syntax throughout the file. This test is performed by the European HFR Node before pushing data to the distribution platforms.
DDNS_QC	Data Density Threshold	<b>Data Density Threshold</b> : this test labels total velocity vectors with a number of contributing radials bigger than the threshold with a “good data” flag and total velocity vectors with a number of contributing radials smaller than the threshold with a “bad data” flag.
CSPD_QC	Velocity Threshold	Velocity <b>Threshold</b> : this test labels total velocity vectors whose module is bigger than a maximum velocity threshold with a “bad data” flag and total vectors whose module is smaller than the threshold with a “good data” flag.
VART_QC	Variance Threshold	<b>Variance Threshold</b> : this test labels total vectors whose temporal variance is bigger than a maximum threshold with a “bad data” flag and total vectors whose temporal variance is smaller than the threshold with a “good data” flag. This test is applicable only to Beam Forming (BF) systems. Data files from Direction Finding (DF) systems will apply instead the “Temporal Derivative” test reporting the explanation “Test not applicable to Direction Finding systems. The Temporal Derivative test is applied.” in the comment attribute.
TIME_QC	Temporal Derivative	<b>Temporal Derivative</b> : for each total bin, the current hour velocity vector is compared with the previous and next hour ones. If the differences are bigger than a threshold (specific for each grid cell and evaluated on the basis of the analysis of one-year-long time series), the present vector is flagged as “bad data”, otherwise it is labelled with a “good data” flag. Since this method implies a one-hour delay in the data provision, the current hour file should have the related QC flag set to 0 (no QC performed) until it is updated to the proper values when the next hour file is generated.
GDOP_QC	GDOP Threshold	<b>GDOP Threshold</b> : this test labels total velocity vectors whose GDOP (Geometrical Dilution Of Precision) is bigger than a maximum threshold with a “bad data” flag and the vectors whose GDOP is smaller than the threshold with a “good data” flag.
QCflag	Overall QC	

**Annex II QC Flags**

Code	Meaning	Comment
0	No QC was performed	-
1	Good data	All real-time QC tests passed.
2	Probably good data	-*
3	Bad data that are potentially correctable	These data are not to be used without scientific correction.*
4	Bad data	Data have failed one or more of the tests.
5	Value changed	Data may be recovered after transmission error.
6	Not used	-
7	Nominal value	-
8	Interpolated value	Missing data may be interpolated from neighbouring data in space or time.

9	Missing value	-
---	---------------	---

\*These two are to be used after examination of the hist data sets and exchanges with the data provider

### Annex III Figures for the QA/QC tests

Fig A – Temporal series of the spatial average of the current velocity module (first panel), its standard deviation (second panel), the grid points of the total coverage (third panel), and monthly data availability. Black dots are the values obtained considering all the data in the domain, in green those considering only data with QC flag =1 (good data).


Fig B - Temporal series of the QC flags for all the grid nodes with data and percentage of data with each flag (0,1,2,3,4).


Fig C - Maps of the mean velocity module and the mean value of QC flags for the target year (left column) and their standard deviations (right column) for the target year.


Fig D - Spatial (x-axis) vs. temporal (y-axis) coverage 80/80 annual metric. Allows to check if the system has reached the goal of providing surface currents over the 80% of the area during 80% of the time. The grid points taken in account for the % are the ones inside the GDOP limits defined by the data provider.


Fig E – Map of the % of availability of data in each grid point and contour showing the area of temporal availability >80%


Fig F- Mean surface current maps for the indicated systems and periods. The means are computed in the area of 80% temporal coverage for the target year.
















































































Version of the report	Changes made by	Nature of changes
VR2023_11	L. Solabarrieta & I. Manso	Updated for 2022
Contact the EU HFR general Node email for more information about this report: <a href="mailto:euhfrnode@azti.es">euhfrnode@azti.es</a>		
Other possible contacts: <a href="mailto:lsolabarrieta@azti.es">lsolabarrieta@azti.es</a> ; <a href="mailto:arubio@azti.es">arubio@azti.es</a> ; <a href="mailto:jmader@azti.es">jmader@azti.es</a> ; <a href="mailto:imanso@azti.es">imanso@azti.es</a>		